












## TECHNICAL INFORMATION / TEKNISK INFORMATION



# BERGO XL

Material:		ISO2076	Environmentally friendly recyclable UV-stabilized polypropylene.	/ Miljövänlig återvinningsbar UV-stabiliserad polypropen.
Size of tile: /Plattans storlek:		EN427	377,2 x 377,2 mm. 1 m <sup>2</sup> / box = 7 tiles. 5 m <sup>2</sup> / box = 35 tiles.	
Thickness of tile: /Plattans tjocklek:		EN428	10,1 mm.	
Weight of tile: /Plattans vikt:		EN430	350 g.	
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	250 ton / 1 m <sup>2</sup> = 2500 kg/dm	
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8	
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5	
Slip resistance: /Halkmotstånd:		SSEN-13893	>0,3	
Impact resistance: /Slagtålighet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m <sup>2</sup> / -20 °C = 5 kJ/m <sup>2</sup> C 15 kJ/m <sup>2</sup>	
Fire category /Brandklassning:		EN ISO 11925-2	E <sub>fl</sub>	
CE certification:		EN 14041	0402-CPD-P605080A	





By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



www.bergoflooring.com

