



World
of SPC
by CHECK ✓

Product information

Guarantee	10 Years*
Wear layer	0.5 mm
Utilisation class	41
Sealing	UV varnish
Chamfer	4V-groove

Dimensions & Packaging

Dimension		1220 x 228 x 4 mm
Packing unit (PU)	1x4	8 Planks = 2.225 sqm
Pallet size	Wide plank	48 PU = 106.813 sqm
Clicksystem		Loc-Click
Dimension		550 x 110 x 4 mm
Packing unit (PU)	1x4	26 Planks = 1.573 sqm
Pallet size	Herringbone	72 PU = 113.256 sqm
Clicksystem		Push-Click

Technische Daten/durchgeführte Prüfungen:

Lightfast	ISO 105-B02	≥ 6
Dimensional stability	ISO 23999	✓
Scratch resistance	EN 438 T2	✓
Fire behavior	EN 13501-1	Bfl, s1
Residual indentation	ISO 24343-1	0.01 mm
Slip resistance	EN 14041	DS
Thermal Conductivity	ISO 12667	0.08 m ² K/W
Underfloor heating	EN 12524	hot water suitable, max 27 °C
Formaldehyde class	EN 717-1	E1
Castor chair resistance	ISO 4918	none damage

* according to guarantee conditions

All specified values are standard values.
Production-related fluctuations can not be ruled out.



Scheuten-Solar-Str. 2 • 45881 Gelsenkirchen • Tel.: +49 209 / 59034-0 • Fax: +49 209 / 59034-29
E-Mail: info@koczwaravertrieb.de • Web: www.koczwaravertrieb.de; check-floors.com